

HS SCM Auto - V2-SK-HA



Black+Golden



Black+Silver



Black+White

A simple, automatic way to apply protective shoe film before entering designated indoor areas.

Fast operation

Approx. 3 seconds per piece

Large roll capacity

Up to 1,000 pieces per roll

Anti-slip film

Compatible with anti-slip film



Product Overview

HS SCM Auto - V2 has a digital display, uses anti-slip shoe film and also include the sterilization function for the higher versions HB and HC versions which are used for hospitals.

Key Specifications

SPECIFICATION	DETAIL
Model	HS SCM Auto - V2
Display screen	Digital screen
Sterilization	No
Compatible shoe film	Anti-slip shoe film
Machine dimensions	66 × 32.8 × 35 cm
Net weight	16.8 kg
Film release speed	Approx. 3 seconds per piece
Film capacity	Up to 1,000 pieces
Power supply	AC 220/110 V, 50/60 Hz
Power rating (as stated in source catalog)	3.7 kW — please confirm with supplier
Internal working voltage	DC 12 V, 5 A
Packing size	72 × 40 × 42 cm
Gross weight	22.6 kg/carton
Packing quantity	1 set per carton

Compatible Film & Usage

Compatible film: SK-H anti-slip shoe film

	Model	anti-slip shoe film	Anti-static shoe film	blue shoe film
	weight/Carton	14.5kg/carton		
	Material	PVC		
	thickness	28µm(average value)		
	Quantity	1000pcs/roll		
	Rolls/Carton	4rolls/carton		
	Size/Roll	Diameter153mm*Length245mm		
	weight/Roll	3.3kg		
	Size/Carton	32*32*25CM		
	weight/Carton	14.5kg/carton		

FILM SPECIFICATION	DETAIL
Film material	PVC / heat-shrink PVC
Average thickness	28 µm (0.028 mm)
Quantity	1,000 pieces per roll
Rolls per carton	4 rolls
Roll dimensions	Approx. 153 mm diameter × 245 mm length
Weight per roll	3.3 kg
Carton size	32 × 32 × 25 cm
Gross carton weight	14.5 kg

How to use

1. Place the shoe on the pedal area, aligning it with the footprint guide.
2. Press down and hold still while the film shrinks and wraps around the shoe.
3. Lift the foot after the film has wrapped. The dispenser feeds the next piece automatically.